


(51) International Patent Classification ⁵ : G03B 27/53, H04N 5/253	A1	(11) International Publication Number: WO 92/05469 (43) International Publication Date: 2 April 1992 (02.04.92)
(21) International Application Number: PCT/US91/06288 (22) International Filing Date: 5 September 1991 (05.09.91) (30) Priority data: 583,420 17 September 1990 (17.09.90) US (71) Applicant: EASTMAN KODAK COMPANY [US/US]; 343 State Street, Rochester, NY 14650-2201 (US). (72) Inventor: COSGROVE, Patrick, Andre ; 82 Troutbeck Lane, Rochester, NY 14626 (US). (74) Agent: DUGAS, Edward; 343 State Street, Rochester, NY 14650-2201 (US).		(81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent). Published <i>With international search report.</i>

(54) Title: **USE OF PRE-SCANNED LOW RESOLUTION IMAGERY DATA FOR SYNCHRONIZING APPLICATION OF RESPECTIVE SCENE BALANCE MAPPING MECHANISMS DURING HIGH RESOLUTION RESCAN OF SUCCESSIVE IMAGES FRAMES ON A CONTINUOUS FILM STRIP**

(57) Abstract

A plurality of color photographic images that have been captured on a continuous color photographic film strip are pre-scanned at low resolution and then rescanned at high resolution by an opto-electronic scanning device and processed for storage as a plurality of digitized images in a digital imagery data base. The film strip contains notches to spatially locate pre-scan frame data during rescan. During pre-scan the film strip is translated past an opto-electronic scanner in a first direction to obtain a plurality of first digitally encoded images. During high resolution rescan, the film strip is translated in the reverse direction. The high resolution imagery data is mapped into image storage memory on the basis of the contents of respective first digitally encoded images. During the rescan the mapping process is calibrated on the basis of information contained on the film strip other than the notches, such as detected interframe gaps and a correlation of low resolution and high resolution frame 'fingerprints'.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland			SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU ⁺	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE*	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

USE OF PRE-SCANNED LOW RESOLUTION IMAGERY DATA
FOR SYNCHRONIZING APPLICATION OF RESPECTIVE SCENE
BALANCE MAPPING MECHANISMS DURING HIGH RESOLUTION
RESCAN OF SUCCESSIVE IMAGES FRAMES ON A
CONTINUOUS FILM STRIP

5

FIELD OF THE INVENTION

The present invention relates in general to digital imagery processing systems and is particularly directed to a scheme for using image frame identification information, derived during a low resolution scan of successive image frames on a continuous film strip, to spatially synchronize the control of a subsequent reverse-direction, high resolution scan of each of previously scanned image frames on a reel of color photographic film containing that film strip.

BACKGROUND OF THE INVENTION

Photofinishing systems customarily prescan a strip of (35mm) film to examine the quality and color content of the respective image frames prior to transferring the images to print paper. On the basis of this prescan examination, exposure control parameters of the imaging optics components are defined so that, during a subsequent pass of the film, the projection of each image onto the print medium will be properly adjusted to yield an acceptable quality hard copy print.

30

In order to demarcate where each image is located on the film strip, respective notches are formed along the edge of the film, for example between successive frames, or centrally of each frame. During rescan, these notches are used to identify successive frames and thereby call up previously defined exposure control parameters for adjusting the projection optics.

35

A shortcoming of such an exposure control procedure is the fact that a notch is sometimes missed. When this happens, there is a mismatch between the current image frame and prescan-derived exposure control parameters. The result is a poor quality set of prints, making it necessary for the photofinisher to reprocess the film strip, which entails additional time, and costs associated with the wasted print materials. Now although a minor lag in processing can be adequately managed, when a large reel of film is to be scanned continuously on a single machine and then printed on the same (or other) machine, it is too complex to track and detect possible sequence errors. As a result, almost no equipment currently available attempts to track such errors over multiple film strips.

SUMMARY OF THE INVENTION

In accordance with the present invention, the above-described spatial synchronization problem is effectively obviated by using supplemental or auxiliary information derived during the prescan of the image, thereby augmenting the function of each notch so that even if a notch is missed during rescan, spatial synchronization between each frame and its associated prescan-derived control information will be maintained. The present invention is particularly applicable to a highly automated digital imagery processing system, wherein successive image frames of a continuous reel of color photographic film, such as a spliced-together sequence of 35mm film strips, are prescanned in a first order at low spatial resolution and then rescanned in reverse order to derive a color balanced, high spatial resolution digitized image for each frame.

In such a digital imagery processing system, each frame on the film is pre-scanned at low resolution, with each digitized image being processed by a scene balance mechanism for deriving control
5 information to be used for optimizing the manner in which a subsequently scanned high resolution digitized image is to be mapped into memory. The scene balance mechanism determines how the response characteristic of the scanner's imaging pixel array sees the image and
10 encodes its spatial content. The output of this analysis, which represents the color balance content of the digitized image, is then used to adjust, or calibrate, the sensitivity parameters of the scanner during the high resolution scan, so that the essential
15 subject matter of the image (i.e. that which is necessary to reproduce a high quality image) will fall within the linear portion of the response range of the scanner's imaging pixel array. The high resolution digitized image is then processed by the scene balance
20 mechanism to map the image data into a digitized image having a reduced encoding resolution corresponding to that of an attendant framestore.

In such a system, should there be a mismatch
25 between prescan imagery data and a high resolution frame, the wrong prescan-based calibration information would be used during the high resolution scan, and an unacceptable image would be mapped into memory. To prevent this from happening, the present invention does
30 not rely exclusively on detecting frame location notches as in conventional (analog) systems, but uses other detected frame identification information that may be used independently of, or in combination with, the notches to improve the reliability of the scanner
35 calibration for each processed image.

Pursuant to the invention, a reel of color photographic film (comprised of one or more spliced together film strips) is initially translated in a first direction past a selectable resolution opto-electronic film scanner which scans the images on the film at a first, low resolution, thereby producing a plurality of first digitally encoded images. For each pre-scanned image a first signal, in the form of a first digital code representative of a prescribed attribute of that scanned image, is generated and stored. This first code may represent a statistical measure of the contents of the image, e.g. a summation of the image contents of each of the columns of the low spatial resolution pixel sub- array. Alternatively, or in addition to the first code, a second code, representative of the location of a respective interframe gap, namely, a separation between successive images on the film strip, may be generated. The location of interframe gaps is readily accomplished by observing what is effectively a stepwise variation in the output of the scanner as non-image regions of the film are scanned during the film's movement past the scanner's imaging optics. Each of the plurality of first digitally encoded images is then processed in accordance with a scene balance mechanism to derive a calibration code representative of the color content of the image.

After the entire reel has been scanned at low resolution and first, second and scanner calibration codes have been stored for each image, the photographic film strip is translated past the opto-electronic scanning device in a reverse direction, so as to effect a rescanning of the plurality of photographic images, but in an order opposite to that of the original scan.

The rescan of each image (which may be conducted on the same or a different film scanner) is conducted at a second, high spatial scanning resolution to produce a plurality of second digitally encoded images. During
5 the rescan of each image, a third signal, in the form of a third digital code, representative of the prescribed attribute of the scanned image, is generated and stored. As in the case of the first code, the third signal may represent a statistical measure of the
10 contents of the image, such as a summation of the image contents of those columns of the image array corresponding to the columns of the low spatial resolution pixel sub-array. Each second digitally encoded image is then mapped into memory using a scene
15 balance mechanism that has been calibrated in accordance with a respective scene balance calibration signal.

To ensure that the correct calibrated scene
20 balance mechanism is employed during the high resolution scan, its selection may be based upon a combination (e.g. correlation) of the first and third statistical measure representative codes, or by looking for the presence of an interframe gap, as represented
25 by the second code, in addition to a frame demarcating notch. Namely, notch information is augmented by other data that is derived during pre-scan of the film.

BRIEF DESCRIPTION OF THE DRAWINGS

30 Figure 1 diagrammatically illustrates a photographic color film photofinishing minilab for continuous processing of a reel of spliced-together color photographic film strips;

35 Figure 2 is an imagery processing flow diagram of a low resolution scene balance based

calibration and high resolution imagery digitizing mechanism;

Figure 3 diagrammatically illustrates an
5 exemplary output of an opto-electronic scanner; and

Figure 4 diagrammatically illustrates a
sequence of image frames on a color photographic film
strip.

10

DETAILED DESCRIPTION

Before describing, in detail, the inventive
use of pre-scanned low resolution imagery data to
synchronize the application of a plurality of scene
15 balance mapping mechanisms during high resolution
scanning of successive images frames on a continuous
film strip, it should be observed that the present
invention resides primarily in a novel structural
combination of conventional digital imagery processing
20 circuits and components and not in the particular
detailed configurations thereof. Accordingly, the
structure, control and arrangement of these
conventional circuits and components have been
illustrated in the drawings by readily understandable
25 block diagrams which show only those specific details
that are pertinent to the present invention, so as not
to obscure the disclosure with structural details which
will be readily apparent to those skilled in the art
having the benefit of the description herein. Thus, the
30 block diagram illustrations of the Figures do not
necessarily represent the mechanical structural
arrangement of the exemplary system, but are primarily
intended to illustrate the major structural components
of the system in a convenient functional grouping,
35 whereby the present invention may be more readily
understood.

Figure 1 diagrammatically illustrates a photographic color film processing system (e.g. photofinishing minilab) with which the present invention may be employed and, for purposes of the present description, such a system may be of the type described in co-pending Patent application Serial Number ___, filed ___, by S. Kristy, entitled "Multi-resolution Digital Imagery Photofinishing System", assigned to the assignee of the present application and the disclosure of which is herein incorporated. It should be observed, however, that the system described in the above-referenced co-pending Kristy application is merely an example of one type of system in which the invention may be used and is not to be considered limitative of the invention. In general, the invention may be incorporated in any digitized imagery processing and reproduction system.

In accordance with the imagery data processing system of the above referenced co-pending Kristy application, each high resolution captured image is preferably formatted and stored as a respective image data file containing a low, or base, resolution image bit map file and a plurality of higher resolution residual images associated with respectively increasing degrees of image resolution. By iteratively combining these higher resolution residual images with the base resolution image, successively increased resolution images may be recovered from the base resolution image. As an example, spatial data values representative of a high resolution (3072 x 2048) image scan of a 36mm-by-24mm image frame of a 35mm film strip may be stored as a respective image data file including a base resolution image bit map file containing data values associated with a spatial image array or matrix of 512

-8-

rows and 768 columns of pixels and an associated set of residual image files to be stored on the disc. Within a photofinishing workstation, the base resolution image may be further sub-sampled to derive an even lower

5 resolution sub-array of image values (e.g. on the order of 128 x 192 pixels) for use by the photofinishing operator in the course of formatting and storing a digitized image file.

10 Thus, in the digital image processing system of Figure 1, color photographic images, such as a set of twenty-four or thirty-six 36mm-by-24mm image frames of a 35mm color film strip 10, are scanned by a high resolution opto- electronic color film scanner 12, such
15 as a commercially available Eikonix Model 1435 scanner. High resolution film scanner 12 outputs digitally encoded data representative of the response of its imaging sensor pixel array (e.g. a 2048 x 3072 pixel matrix) onto which a respective photographic image
20 frame of film strip 10 has been projected by an input imaging lens system. This digitally encoded data, or 'digitized' image, is encoded to some prescribed resolution (e.g. sixteen bits per color per pixel) that encompasses a range of values over which the contents
25 of the scene on the color film may vary. For a typical color photographic negative, the range of values is less than the density vs. exposure latitude of the film, but is sufficiently wide to encompass those density values that can be expected to be encountered
30 for a particular scene. Also shown in Figure 1 is a notch detector 17 which detects frame location notches in film strip 10 for synchronization purposes, as will be described below.

35 Because of its very large (2048 x 3072) spatial resolution, with the output of each pixel being

resolved to sixteen bits, the quantity of data per image produced by such high resolution film scanners is so large that it must be reduced for storage and reasonably fast access in a practical sized framestore, 5 which necessarily implies that some of the scene information in the digitized image will be discarded. For this purpose, a scene balancing mechanism is used to map the digitized image into a set of lower resolution digital codes (e.g. eight bits per color per 10 pixel), each of which has a resolution corresponding to the dynamic range of a digitized image data base (framestore). The database may be resident in a photofinishing workstation 14, which contains imagery application software through which the digitized image 15 may be processed to achieve a desired base image appearance and configuration in the course of driving a high resolution thermal printer 16 to output a high quality color print.

20 Preferably, in the course of being mapped into memory, the digitized imagery data output by the high resolution film scanner is subjected to a code conversion mechanism of the type described in co-pending application Serial No. ___, filed ___, by T. 25 Madden et al, entitled "Extending Dynamic Range of Stored Image Database," assigned to the assignee of the present application and the disclosure of which is herein incorporated. Pursuant to this code conversion scheme, the dynamic range of the digitized image 30 database may be extended to permit shifting of encoded pixel values without 'clipping', and to provide a limited window of values into which extremely high reflectance image points may be encoded and stored. To this end, digital codes, into which the high resolution 35 imagery data output by the image scanner are mapped by the scene balance mechanism, are converted into a set

-10-

of reduced-range digital codes of the same resolution as, but having a smaller range of image content values than the dynamic range of the digitized image data base. The code conversion mechanism operates to convert
5 a maximum value of 100% white reflectance to an encoded value that is less than the upper limit of the dynamic range of the database to accommodate shifts in the digitized imagery data and allow for the placement of specular highlights that are beyond the 100% white
10 reflectance maximum.

When digitizing an image during a high resolution scan, the response of the scanner is calibrated such that the principal subject matter of
15 the image falls within the linear portion of the response range of the scanner's imaging pixel array. For this purpose, as described in my co-pending application Serial No. ____, filed ____, entitled "Scene Balance Calibration of Digital Scanner", assigned to
20 the assignee of the present application and the disclosure of which is herein incorporated, the digital imagery processing system employs a calibration and high resolution capture procedure, diagrammatically illustrated in the imagery processing flow diagram of
25 Figure 2, whereby the image is scanned twice, once at low resolution for purposes of calibration, and then at high resolution, for data capture.

More particularly, as shown at step 101,
30 image scanner 12 is controlled to carry out a low resolution mode, prescan of an image 10 of interest. Where the scanner has multiple resolution scan capability, it is controlled so as to scan the image at a relatively low spatial resolution, e.g. on the order
35 of 24 x 36 pixels per frame. Depending upon the size of the low resolution image, it may be necessary to

perform a further spatial compression of the captured image, in order to reduce the computational intensity (and thereby achieve a reasonably rapid throughput) of the application of the low resolution image to a scene balance mechanism. In accordance with the multiple mode operation of the above- referenced high resolution scanner, during low resolution scan, a 128 x 192 image is captured. Through further spatial integration of the imagery data within workstation 14, the captured 128 x 192 pixel version of the image may be reduced to a very small sub-array (e.g. 24 x 36 pixels, each encoded at sixteen bits per color) for application to the scene balance mechanism through which high resolution imagery data is mapped into the framestore.

15 This very low resolution (24 x 36) digitized image is then analyzed in step 102 by the scene balance mechanism to determine how the response characteristic of the scanner's imaging pixel array sees the image and encodes its spatial content. The scene balance mechanism (the processed result of which may be implemented as a set of look-up tables (LUTs), one for each RGB color) outputs three values, one for each color, which represent the color balance content of the digitized image.

In step 103, using these values, the sensitivity of the scanner is calibrated, so that, during a subsequent high resolution scan of the image, the essential subject matter of the image will fall within the linear portion of the response range of the scanner's imaging pixel array. While the scene balance output values may be employed to effect vernier adjustments of reference voltages for the scanner's imaging array, in accordance with a preferred mode of the present invention, a respective offset code, one

-12-

for each of the color values, is added to the inputs of each scene balance look-up table in order to effectively shift or translate its mapping function that brings the essential subject matter of the image
5 into the linear portion of the response range of the scanner's imaging pixel array.

With the scanner now calibrated, (e.g. scene balance look-up tables shifted to optimize the use of
10 the imaging array's linear response range), the scanner is controlled in step 104 to execute a high resolution scan of the image. Since the scene balance LUTs have been translated in accordance with the output of the low resolution prescan, the high resolution digitized
15 image will be mapped into the framestore such that essential image information (i.e. that which is necessary to obtain a high quality print) is captured and stored.

20 As pointed out above, in a highly automated photofinishing system, wherein successive image frames of a continuous reel of color photographic film, such as a spliced-together sequence of 35mm film strips, are prescanned at low spatial resolution and then rescanned
25 to derive a color balanced, high spatial resolution digitized image, there is a potential problem of image misalignment or lack of image synchronization between the low and high resolution scans. Namely, should there be a mismatch between prescan imagery data and a high
30 resolution frame, the wrong prescan-based calibration information would be used during the high resolution scan, and an unacceptable image mapped into memory.

To prevent such misalignment, the present
35 invention employs a synchronization scheme that does not rely exclusively on detecting frame location

notches, but uses other detected frame identification information independently or in combination with the notches to improve the reliability of the scanner calibration for each processed image. Pursuant to the invention, when the reel of color photographic film (comprised of one or more spliced together film strips) is initially scanned at low resolution by the opto-electronic film scanner, a plurality of first digital codes, each of which representative of a prescribed attribute of a respective scanned image, is generated and stored.

As diagrammatically illustrated in Figure 3, which shows an exemplary output of an opto-electronic scan of film strip 10, a portion of which is shown in Figure 4, this first code may represent a statistical measure of the contents of an image frame, e.g. a summation of the image contents of each of the columns 201 of the low spatial resolution pixel sub-array. Alternatively, or in addition to the first code, a second code, representative of the location of a respective interframe gap 205, for example, a separation between successive image frames 210, 211 on the film strip 10, may be generated. The location of interframe gaps 205, whereat frame registration notches 206 along the edge of the film should be placed, is readily accomplished by observing what is effectively a stepwise variation 207 in the output of the scanner as non-image regions 209 of the film are scanned during the film's movement past the scanner's imaging optics. Each of the plurality of first digitally encoded images is then processed in accordance with the scene balance mechanism, as described above, to derive a calibration code representative of the color content of the image.

-14-

After the entire reel has been scanned at low resolution and first and second codes stored for each image, photographic film strip 10 is translated past the opto- electronic scanning device in a reverse direction, so as to effect a rescanning of the plurality of photographic images, but in an order opposite to that of the original scan. The rescan of each image is conducted at a second, high spatial scanning resolution to produce a plurality of second digitally encoded images. During the rescan of each image, a third signal, in the form of a third digital code, representative of the prescribed attribute of the scanned image, is generated and stored. As in the case of the first code, the third signal may represent a statistical measure of the contents of the image, such as a summation of the image contents of those columns of the image array corresponding to the columns of the low spatial resolution pixel sub-array. Each second digitally encoded image is then mapped into memory using a scene balance mechanism that has been calibrated in accordance with a respective scene balance calibration signal, as described above with reference to Figure 2.

To ensure that the correct calibrated scene balance mechanism is employed during the high resolution scan, its selection may be based upon a combination (correlation) of the first and third statistical measure representative codes, or by looking for the presence of interframe gap 205, as represented by the second code, in addition to frame-demarcating notch 206. Namely, the output of a notch detector 17, which looks for the presence of notches during the rescan, is augmented by other data that is derived during pre-scan of the film. For this purpose, the output of notch detector 17 and the second code signal

may be logically combined (e.g. ORed) to identify the location of the successive image frames. Notch detection may also be supplemented by comparing how closely (within a prescribed window), the first and third statistical measure codes match. In effect, each first and third code may be considered to be a 'fingerprint' of the image. If these 'prints' match, it is inferred that the correct scene balance calibration has been selected for the image of interest, so that the manner in which each successive high resolution digitized image is mapped into memory will be optimized, so that the essential subject matter of each image will fall within the linear portion of the response range of the scanner's imaging pixel array. The high resolution digitized image is then mapped by the scene balance mechanism into a reduced encoding resolution framestore.

As will be appreciated from the foregoing description, the 'missed notch' spatial synchronization problem encountered in multiscan photofinishing operations is effectively obviated in accordance with the present invention by the use of auxiliary information derived during the prescan of the image. This auxiliary information is used to supplement the frame-locating function of each notch, so that even if a notch is missed during the high resolution scan, spatial synchronization between each frame and its associated prescan-derived control information will be maintained. As a consequence, the present invention is particularly applicable to a highly automated digital imagery processing system, wherein successive image frames of a continuous reel of color photographic film, such as a spliced-together sequence of 35mm film strips, are prescanned at low spatial resolution and then rescanned to derive a color balanced, high spatial

resolution digitized image.

While I have shown and described an embodiment in accordance with the present invention, it
5 is to be understood that the same is not limited thereto but is susceptible to numerous changes and modifications as known to a person skilled in the art, and I therefore do not wish to be limited to the details shown and described herein but intend to cover
10 all such changes and modifications as are obvious to one of ordinary skill in the art.

WHAT IS CLAIMED

1. A method of controlling the manner in which a plurality of color photographic images that
5 have been captured on a continuous color photographic film strip are scanned by an opto-electronic scanning device and processed for storage as a plurality of digitized images in a digital imagery data base, said film strip containing physical demarcations associated
10 with the locations of respective ones of said images thereon, comprising the steps of:

(a) translating said photographic film strip with respect to said opto-electronic scanning device so as to effect a sequential scanning of said plurality of
15 photographic images at a first, low spatial scanning resolution and thereby producing a plurality of first digitally encoded images;

(b) translating said photographic film strip with respect to said opto-electronic scanning device so
20 as to effect a sequential rescanning of said plurality of photographic images at a second, high spatial scanning resolution and thereby producing a plurality of second digitally encoded images;

(c) mapping respective ones of said plurality
25 of second digitally encoded images into image storage memory on the basis of the contents of respective ones of said plurality of first digitally encoded images, selected on the basis of information contained on said film strip other than said physical demarcations.

30

2. A method according to claim 1, wherein step (c) comprises mapping respective ones of said plurality of second digitally encoded images into image storage memory on the basis of the contents of
35 respective ones of said plurality of first digitally encoded images, selected on the basis of a combination

-18-

of information contained on said film strip other than said physical demarcations with information representative of said physical demarcations.

5 3. A method according to claim 1, wherein said physical demarcations correspond to notches in said film strip.

10 4. A method according to claim 1, wherein, in step (c), said selected other information is representative of the separation between successive images captured on said photographic film strip.

15 5. A method according to claim 1, wherein step (a) comprises translating said photographic film strip in a first direction relative to said opto-electronic scanning device, so as to scan successive ones of first through N photographic images on said film strip, and step (b) comprises translating said
20 photographic film strip in a second, reverse direction, relative to said opto- electronic scanning device, so as to scan successive ones of N through first photographic images on said film strip.

25 6. A method according to claim 1, wherein, in step (c), said selected other information includes information contained in said first and second digitally encoded images.

30 7. A method of controlling the manner in which a plurality of color photographic images that have been captured on a color photographic image recording medium are scanned by an opto-electronic scanning device and processed for storage as a plurality of digitized images in a digital imagery data
35 base, comprising the steps of:

(a) scanning said plurality of photographic images at a first, low resolution to produce a plurality of first digitally encoded images, and processing each first digitally encoded image in accordance with a prescribed image processing mechanism to derive, for each image, a first signal representative of a first prescribed attribute of said image;

(b) generating second signals representative of separations between successive ones of images as captured on said photographic recording medium;

(c) generating third signals representative of physical demarcations associated with the locations of respective ones of said plurality of images on said photographic recording medium;

(d) rescanning said plurality of photographic images at a second, high resolution, to produce a plurality of second digitally encoded images, and processing each second digitally encoded image in accordance with said prescribed image processing mechanism adjusted in accordance with a respective one of the first signals produced in step (a) and selected in accordance with a prescribed relationship between said second and third signals.

25

8. A method according to claim 7, wherein said prescribed image processing mechanism comprises a scene balance mechanism and wherein said first prescribed attribute corresponds to image color content.

9. A method according to claim 7, wherein step (a) further comprises generating fourth signals representative of a second prescribed attribute of each of said first digitally encoded images, and step (d) further comprises generating fifth signals

35

representative of said second prescribed attribute of each of said second digitally encoded images and wherein each second digitally encoded image is processed in accordance with a prescribed relationship
5 between said fourth and fifth signals.

10. A method of controlling the manner in which a plurality of color photographic images that have been captured on a color photographic image
10 recording medium are scanned by an opto-electronic scanning device and processed for storage as a plurality of digitized images in a digital imagery data base, comprising the steps of:

(a) scanning said plurality of photographic
15 images at a first, low resolution to produce a plurality of first digitally encoded images, and processing each first digitally encoded image in accordance with a scene balance mechanism to derive, for each image, a first signal representative of the
20 color content of said image, and producing, for each image, a second signal representative of a prescribed attribute of that image; and

(d) rescanning said plurality of photographic images at a second, high resolution, to produce a
25 plurality of second digitally encoded images, and producing for each second image a third signal representative of said prescribed attribute of that image, and processing each second digitally encoded image in accordance with a scene balance mechanism that
30 has been calibrated in accordance with a respective one of the first signals produced in step (a) and selected in accordance with a prescribed relationship between said second and third signals, so as to obtain a color content-balanced digitized image.

35

11. A method according to claim 10, wherein
step (a) comprises scanning said photographic recording
medium in a first direction so as to scan successive
ones of first through N photographic images, and step
5 (b) comprises scanning said photographic recording
medium in a second, reverse direction, so as to scan
successive ones of N though first photographic images.

12. A method of controlling the manner in
10 which a plurality of color photographic images that
have been captured on a color photographic image
recording film strip are scanned by an opto-electronic
scanning device and processed for storage as color-
balanced digitized images in a digital imagery data
15 base, comprising the steps of:

(a) scanning said color photographic images
by means of said opto-electronic device so as to obtain
a first digitally encoded images and generating first
signals representative of separations between
20 successive ones of said color photographic images on
said film strip;

(b) generating second signals representative
of physical demarcations in said film strip
representative of the locations of respective ones of
25 said color photographic images;

(c) processing each of said first digitally
encoded images in accordance with a scene balance
mechanism and producing a respective third signal
representative of the manner in which said opto-
30 electronic scanning device encodes the color content of
said each color photographic image;

(d) rescanning said color photographic image
by means of said opto-electronic scanning device so as
to obtain a second digitally encoded image; and

35 (e) processing said second digitally encoded
image in accordance with said scene balance mechanism,

calibrated by said third signal produced in step (b),
said third signal being selected in accordance with a
prescribed relationship between said first and second
signals, so as to obtain a color content-balanced
5 digitized image for storage in said digital imagery
database.

13. A method according to claim 12, wherein
step (a) comprises scanning said plurality of color
10 photographic images by means of said opto-electronic
device so as to obtain a plurality of first digitally
encoded images having a first spatial resolution, and
step (d) comprises rescanning said color photographic
images by means of said opto-electronic scanning device
15 so as to obtain a plurality of second digitally encoded
images having a second spatial resolution, larger than
said first spatial resolution.

14. A method according to claim 12, wherein
20 step (a) comprises scanning said plurality of color
photographic images by means of said opto-electronic
device so as to obtain a plurality of first digitally
encoded images of said first spatial resolution and a
first encoding resolution, and step (d) comprises
25 rescanning said plurality of color photographic images
by means of said opto-electronic scanning device so as
to obtain a plurality of second digitally encoded
images of said second spatial resolution, and a second
encoding resolution less than said first encoding
30 resolution.

15. A method of controlling the manner in
which a plurality of color photographic images that
have been captured on a continuous color photographic
35 film strip are scanned by an opto-electronic scanning
device and processed for storage as a plurality of

digitized images in a digital imagery data base,
comprising the steps of:

- 5 (a) translating said photographic film strip
with respect to said opto-electronic scanning device so
as to effect a sequentially scanning of said plurality
of photographic images at a first, low spatial scanning
resolution and thereby produce a plurality of first
digitally encoded images;
- 10 (b) producing, for each image scanned in
step (a), a first signal representative of a prescribed
attribute of that scanned image;
- 15 (c) processing each first digitally encoded
image in accordance with a scene balance mechanism to
derive, for each image, a second signal representative
of the color content of said image;
- 20 (d) translating said photographic film strip
with respect to said opto-electronic scanning device so
as to effect a rescanning of said plurality of
photographic images at a second, high spatial scanning
resolution and thereby produce a plurality of second
digitally encoded images;
- 25 (e) producing, for each image scanned in
step (d), a third signal representative of said
prescribed attribute of that scanned image; and
- 30 (f) processing each second digitally encoded
image in accordance with a scene balance mechanism that
has been calibrated in accordance with a respective one
of the second signals produced in step (c) and selected
in accordance with a prescribed relationship between
said first and third signals.

16. A method according to claim 15, wherein
step (a) comprises translating said photographic film
strip in a first direction relative to said opto-
35 electronic scanning device, so as to scan successive
ones of first through N photographic images on said

film strip, and step (d) comprises translating said photographic film strip in a second, reverse direction, relative to said opto- electronic scanning device, so as to scan successive ones of N through first
5 photographic images on said film strip.

17. A method of controlling the manner in which a plurality of color photographic images that have been captured on a continuous color photographic
10 film strip are scanned by an opto-electronic scanning device and processed for storage as a plurality of digitized images in a digital imagery data base, comprising the steps of:

(a) translating said photographic film strip
15 with respect to said opto-electronic scanning device so as to effect a sequential scanning of said plurality of photographic images at a first, low spatial scanning resolution and thereby produce a plurality of first digitally encoded images;

20 (b) generating first signals representative of physical demarcations associated with the locations of respective ones of said images on said photographic film strip;

(c) generating second signals representative
25 of separations between successive ones of images captured on said photographic film strip;

(d) processing each first digitally encoded image in accordance with a scene balance mechanism to derive, for each image, a third signal representative
30 of the color content of said image;

(e) translating said photographic film strip with respect to said opto-electronic scanning device so as to effect a rescanning of said plurality of photographic images at a second, high spatial scanning
35 resolution and thereby produce a plurality of second digitally encoded images;

(f) processing each second digitally encoded image in accordance with a scene balance mechanism that has been calibrated in accordance with a respective one of the third signals produced in step (c) and selected in accordance with a prescribed relationship between said first and second signals.

18. A method according to claim 17, wherein step (a) comprises translating said photographic film strip in a first direction relative to said opto-electronic scanning device, so as to scan successive ones of first through N photographic images on said film strip, and step (d) comprises translating said photographic film strip in a second, reverse direction, relative to said opto-electronic scanning device, so as to scan successive ones of N through first photographic images on said film strip.

19. An apparatus for controlling the manner in which a plurality of color photographic images that have been captured on a continuous color photographic film strip are scanned and processed for storage as a plurality of digitized images in a digital imagery data base, said film strip containing physical demarcations associated with the locations of respective ones of said images thereon, comprising, in combination:

an opto-electronic scanning device arranged to optically scan said film strip during mutual relative translation of said film strip with respect to said scanning device;

means for translating said photographic film strip with respect to said opto-electronic scanning device so that said scanning device sequentially scans said plurality of photographic images at a first, low spatial scanning resolution and produces a plurality of

first digitally encoded images, and thereafter translating said photographic film strip with respect to said opto- electronic scanning device so that said scanning device sequentially rescans said plurality of photographic images at a second, high spatial scanning resolution and produces a plurality of second digitally encoded images; and

an image processor which maps respective ones of said plurality of second digitally encoded images into an image storage memory on the basis of the contents of respective ones of said plurality of first digitally encoded images, selected on the basis of information contained on said film strip other than said physical demarcations.

15

20. An apparatus according to claim 19, wherein said image processor includes means for mapping respective ones of said plurality of second digitally encoded images into said image storage memory on the basis of the contents of respective ones of said plurality of first digitally encoded images, selected on the basis of a combination of information contained on said film strip other than said physical demarcations with information representative of said physical demarcations.

25

21. An apparatus according to claim 19, wherein said selected other information is representative of the separation between successive images captured on said photographic film strip.

30

22. An apparatus according to claim 19, wherein said translating means includes means for translating said photographic film strip in a first direction relative to said opto-electronic scanning device, so as to scan successive ones of first through

35

N photographic images on said film strip, and thereafter translating said photographic film strip in a second, reverse direction, relative to said optoelectronic scanning device, so as to scan successive
5 ones of N through first photographic images on said film strip.

23. An apparatus according to claim 19, wherein said selected other information includes
10 information contained in said first and second digitally encoded images.

24. An apparatus for scanning a plurality of color photographic images that have been captured on a
15 color photographic image recording medium and processing scanned images for storage as a plurality of digitized images in a digital imagery data base, comprising, in combination:

an optoelectronic scanning device, optically
20 coupled with said color photographic recording medium so as to optically scan said plurality of photographic images at a first, low resolution and producing a plurality of first digitally encoded images;

second means for generating first signals
25 representative of separations between successive ones of images as captured on said photographic recording medium; and

imagery data processing means for processing each first digitally encoded image in accordance with a
30 prescribed image processing mechanism to derive, for each image, a second signal representative of a first prescribed attribute of said image, and third signals representative of physical demarcations associated with the locations of respective ones of said plurality of
35 images on said photographic recording medium; and wherein

said opto-electronic scanning device is controlled to rescan said plurality of photographic images at a second, high resolution, thereby producing a plurality of second digitally encoded images, and wherein said imagery data processing means processes each second digitally encoded image in accordance with said prescribed image processing mechanism that has been adjusted in accordance with a respective one of said second signals and selected in accordance with a prescribed relationship between said first and third signals.

25. An apparatus according to claim 24, wherein said prescribed image processing mechanism comprises a scene balance mechanism and wherein said first prescribed attribute corresponds to image color content.

26. An apparatus for scanning a plurality of color photographic images that have been captured on a color photographic image recording medium processing scanned images for storage as a plurality of digitized images in a digital imagery data base, comprising, in combination:

an opto-electronic scanning device, optically coupled with said color photographic recording medium so as to optically scan said plurality of photographic images at a first, low resolution and producing a plurality of first digitally encoded images;

imagery data processing means for processing each first digitally encoded image in accordance with a scene balance mechanism to derive, for each image, a first signal representative of the color content of said image, and producing, for each image, a second signal representative of a prescribed attribute of that

image; and wherein

5 said opto-electronic scanning device is
controlled to rescan said plurality of photographic
images at a second, high resolution, to produce a
10 plurality of second digitally encoded images, and
producing, for each second image, a third signal
representative of said prescribed attribute of that
image, and wherein said imagery data processing means
includes means for processing each second digitally
15 encoded image in accordance with a scene balance
mechanism that has been calibrated in accordance with a
respective one of said first signals and selected in
accordance with a prescribed relationship between said
second and third signals, so as to obtain a color
20 content-balanced digitized image.

27. An apparatus according to claim 26,
wherein said opto-electronic scanner scans said
photographic recording medium in a first direction so
25 as to scan successive ones of first through N
photographic images, and thereafter scans said
photographic recording medium in a second, reverse
direction, so as to scan successive ones of N through
first photographic images.

25

28. An apparatus for scanning a plurality of
color photographic images that have been captured on a
color photographic image recording film strip and
processing scanned images for storage as color-balanced
30 digitized images in a digital imagery data base,
comprising, in combination:

an opto-electronic scanning device which
scans said color photographic images so as to obtain a
first digitally encoded images and generating first
35 signals representative of separations between
successive ones of said color photographic images on

-30-

said film strip;

means for generating second signals
representative of physical demarcations in said film
strip associated with the locations of respective ones
5 of said color photographic images; and

digital imagery data processing means for
processing each of said first digitally encoded images
in accordance with a scene balance mechanism and
producing therefor a respective third signal
10 representative of the manner in which said opto-
electronic scanning device encodes the color content of
said each color photographic image;

said opto-electronic scanning device
rescanning said color photographic image so as to
15 obtain a second digitally encoded image, and said
digital imagery data processing means processing said
second digitally encoded image in accordance with said
scene balance mechanism, calibrated by said third
signal, said third signal being selected in accordance
20 with a prescribed relationship between said first and
second signals, so as to obtain a color content-
balanced digitized image for storage in said digital
imagery database.

25 29. An apparatus according to claim 28,
wherein said opto-electronic scanning device scans said
plurality of color photographic images so as to obtain
a plurality of first digitally encoded images having a
first spatial resolution, and thereafter rescans said
30 color photographic images, so as to obtain a plurality
of second digitally encoded images having a second
spatial resolution, larger than said first spatial
resolution.

35 30. An apparatus for controlling the manner
in which a plurality of color photographic images that

have been captured on a continuous color photographic recording medium are scanned, processed for storage as a plurality of digitized images in a digital imagery data base and reproduced, said recording medium

- 5 containing physical demarcations associated with the locations of respective ones of said images thereon, comprising, in combination:

an opto-electronic scanning device arranged to optically scan said photographic recording medium
10 during mutual relative translation of said photographic recording medium with respect to said scanning device;

means for translating said photographic recording medium with respect to said opto-electronic scanning device so that said scanning device
15 sequentially scans said plurality of photographic images at a first, low spatial scanning resolution and produces a plurality of first digitally encoded images, and thereafter translating said photographic recording medium with respect to said opto-electronic scanning
20 device so that said scanning device sequentially rescans said plurality of photographic images at a second, high spatial scanning resolution and produces a plurality of second digitally encoded images;

an image processor which maps respective ones
25 of said plurality of second digitally encoded images into an image storage memory on the basis of the contents of respective ones of said plurality of first digitally encoded images, selected on the basis of information contained on said photographic recording
30 medium other than said physical demarcations; and

an image reproduction device for reproducing images captured on said photographic recording medium in accordance with the operation of said image processor.

31. An apparatus according to claim 29,
wherein said image processor includes means for mapping
respective ones of said plurality of second digitally
encoded images into said image storage memory on the
5 basis of the contents of respective ones of said
plurality of first digitally encoded images, selected
on the basis of a combination of information contained
on said photographic recording medium other than said
physical demarcations with information representative
10 of said physical demarcations.

32. An apparatus according to claim 29,
wherein said selected other information is
representative of the separation between successive
15 images captured on said photographic photographic
recording medium.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No PCT/US 91/06288

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶ According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: G 03 B 27/53, H 04 N 5/253														
II. FIELDS SEARCHED <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Minimum Documentation Searched⁷</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; border-bottom: 1px solid black;">Classification System</th> <th style="border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="height: 40px; vertical-align: bottom; border-right: 1px solid black; border-bottom: 1px solid black;">IPC5</td> <td style="border-bottom: 1px solid black;">G 03 B H 04 N</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Documentation Searched other than Minimum Documentation to the extent that such Documents are Included in Fields Searched⁸</div>			Classification System	Classification Symbols	IPC5	G 03 B H 04 N								
Classification System	Classification Symbols													
IPC5	G 03 B H 04 N													
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%; border-bottom: 1px solid black;">Category *</th> <th style="width: 70%; border-bottom: 1px solid black;">Citation of Document,¹¹ with indication, where appropriate, of the relevant passages¹²</th> <th style="width: 20%; border-bottom: 1px solid black;">Relevant to Claim No.¹³</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">P, A</td> <td style="padding: 5px;">WO, A1, 9100673 (EASTMAN KODAK COMPANY) 10 January 1991, see the whole document --</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-32</td> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="padding: 5px;">US, A, 4523839 (B PAYRHAMMER ET AL) 18 June 1985, see abstract; figure 2 --</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-32</td> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="padding: 5px;">Patent Abstracts of Japan, Vol 9, No 310, E364, abstract of JP 60-144078, publ 1985-07-30 FUJI SHASHIN FILM K.K. --</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-32</td> </tr> </tbody> </table>			Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	P, A	WO, A1, 9100673 (EASTMAN KODAK COMPANY) 10 January 1991, see the whole document --	1-32	A	US, A, 4523839 (B PAYRHAMMER ET AL) 18 June 1985, see abstract; figure 2 --	1-32	A	Patent Abstracts of Japan, Vol 9, No 310, E364, abstract of JP 60-144078, publ 1985-07-30 FUJI SHASHIN FILM K.K. --	1-32
Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³												
P, A	WO, A1, 9100673 (EASTMAN KODAK COMPANY) 10 January 1991, see the whole document --	1-32												
A	US, A, 4523839 (B PAYRHAMMER ET AL) 18 June 1985, see abstract; figure 2 --	1-32												
A	Patent Abstracts of Japan, Vol 9, No 310, E364, abstract of JP 60-144078, publ 1985-07-30 FUJI SHASHIN FILM K.K. --	1-32												
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents:¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>														
IV. CERTIFICATION <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;"> Date of the Actual Completion of the International Search 20th December 1991 </td> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;"> Date of Mailing of this International Search Report <div style="text-align: right; font-size: 1.2em;">08 JAN 1992</div> </td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;"> International Searching Authority <div style="text-align: center; font-weight: bold;">EUROPEAN PATENT OFFICE</div> </td> <td style="border-bottom: 1px solid black; padding: 5px;"> Signature of Authorized Officer <div style="text-align: right;"> MISS T. TAZELAAR </div> </td> </tr> </table>			Date of the Actual Completion of the International Search 20th December 1991	Date of Mailing of this International Search Report <div style="text-align: right; font-size: 1.2em;">08 JAN 1992</div>	International Searching Authority <div style="text-align: center; font-weight: bold;">EUROPEAN PATENT OFFICE</div>	Signature of Authorized Officer <div style="text-align: right;"> MISS T. TAZELAAR </div>								
Date of the Actual Completion of the International Search 20th December 1991	Date of Mailing of this International Search Report <div style="text-align: right; font-size: 1.2em;">08 JAN 1992</div>													
International Searching Authority <div style="text-align: center; font-weight: bold;">EUROPEAN PATENT OFFICE</div>	Signature of Authorized Officer <div style="text-align: right;"> MISS T. TAZELAAR </div>													

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
A *	Patent Abstracts of Japan, Vol 9, No 224, P387, abstract of JP 60- 80831, publ 1985-05-08 FUJI SHASHIN FILM K.K. ----- -----	1-32

Form PCT/ISA/210 (extra sheet) (January 1985)

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. PCT/US 91/06288**

SA 51619

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 31/10/91. The European Patent office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A1- 9100673	10/01/91	US-A- 4934821	19/06/90
US-A- 4523839	18/06/85	CH-A-B- 659716	13/02/87
		DE-A-C- 3205898	25/08/83

For more details about this annex : see Official Journal of the European patent Office, No. 12/82